

M | Scaffold

PRODUCT SPECIFICATIONS

COLLECTION	Infrastructure
STYLE NUMBER	I0519
PRODUCT TYPE	Tile
CONSTRUCTION	Multi-Level Pattern Loop
FIBER TYPE	Eco Solution Q® Nylon
DYE METHOD	100% Solution Dyed
PRIMARY BACKING	Non-Woven Synthetic
SECONDARY BACKING	EcoWorx® Tile
TRAFFIC RATING	Heavy
PROTECTIVE TREATMENTS	SSP® Shaw Soil Protection
GSA APPROVED PRODUCT	Yes

	US Units	Metric Units
PRODUCT SIZE	24 inches x 24 inches	60.96 cm x 60.96 cm
AREA PER BOX	48 ft ²	4.46 m ²
PIECES PER BOX	12	
GAUGE	1/10 inches	39.37 per 10 cm
STITCHES	10 per inches	38.71 per 10 cm
FINISHED PILE THICKNESS	0.071 inches	1.80 mm
AVERAGE DENSITY	8113 oz/yd ³	9.07
TOTAL THICKNESS	0.229 inches	5.82 mm
TUFTED YARN WEIGHT	16 oz/yd ²	542.49 g/m ²

Performance Testing

PILL TEST	Pass
RADIANT PANEL	Class I
NBS SMOKE	Less than 450
ELECTROSTATIC PROPENSITY	Less than 3.5 kv
CRI GREENLABEL PLUS	GLP9968
ADA COMPLIANCE	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranty

Lifetime Commercial Limited

Please visit patcraft.com for the most current warranty information.

Installation Methods



Quarter Turn Random Monolithic Brick Ashlar

[Installation Guidelines](#)

[Maintenance Guidelines](#)

M | Scaffold

Environmental Specifications

RECYCLABILITY 100% recyclable

Materials

Ingredients

DOES NOT CONTAIN does not contain PVC, phthalates or PBD/PBDE

Recycled Content

TOTAL RECYCLED CONTENT (BY WEIGHT) 38%

PRE-CONSUMER 38%

POST-CONSUMER 0%

COUNTRY OF ORIGIN (MANUFACTURER) US

Meets or exceeds all local and national regulations in country of manufacture. Manufactured in an ISO9001 & ISO14001 certified facility or equivalent. Recycled content is calculated using system allocation, mass balance, and direct insertion. The actual recycled content in this product will likely vary. For more information email info@patcraft.com.

Third Party Certifications

CRADLE TO CRADLE CERTIFIED®	Silver Certified
NSF 140	Gold Certified
CRI GREEN LABEL PLUS	Certified GLP 9968
USGBC LEED	contributes
BUILDING RESEARCH ESTABLISHMENT	certified
GOOD ENVIRONMENTAL CHOICE AUSTRALIA	certified

Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate specification changes without notice. This carpet is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another carpet design is also strictly prohibited. Visit patcraft.com/testing for more information.

R | Adesa PRODUCT SPECIFICATIONS



COLLECTION	Adesa
STYLE NUMBER	I424V
CONSTRUCTION	Multilayer SPC with Attached Cork Underlayment
ATTACHED UNDERLAYMENT	1.5 mm Cork
WEAR LAYER THICKNESS	20 mil / 0.02 inches (0.508 mm)
OVERALL THICKNESS	0.217 inches (5.5 mm)
EDGE PROFILE	Micro-Bevel
REFERENCE SPECIFICATION	ASTM F3261
FINISH	ExoGuard™
INSTALLATION TYPE	Click
INSTALLATION	Floating, Glue Down
RECOMMENDED ADHESIVE	LOKWORX+ RESILI or 4151

Packaging

	US Units	Metric Units
PLANK SIZE	7.2 inches W x 48.03 inches L	18.3 cm W x 122 cm L
PIECES /BOX	12	
AREA /BOX	28.84 sq ft	2.7 sq m
WEIGHT /BOX	50 lbs	22.7 kg

Performance Testing

STATIC LOAD / ASTM F970	Passes
RESIDUAL INDENTATION / ASTM F1914	Passes
RESISTANCE TO CHEMICALS / ASTM F925	Passes
RADIANT PANEL / ASTM E648	Passes, Class I
SMOKE DENSITY / ASTM E662	Passes
SLIP RESISTANCE / ASTM D2047	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.


Warranty

15 Year Limited Commercial.

Please visit patcraft.com for the most current warranty information.

R | Adesa

Installation Methods



Stagger

[Installation Guidelines](#)

[Maintenance Guidelines](#)

Environmental

GREENGUARD (CERTIFICATION, GOLD, PRIVATE LABEL)

Certified