


Big Splash! Modular

Product Specifications

Collection Name	pdQ1	
Style Number	I0166	
Product Type	Modular	
Construction	Pattern Loop	
Fiber Type	Eco Solution Q® Nylon	
Dye Method	80% Solution Dyed / 20% Yarn Dyed	
	English	Metric
Gauge	1/10	39.37 per 10 cm
Stitches Per Inch	10.0	39.37 per 10 cm
Tufted Pile Height	5/32"	3.97mm
Tufted Yarn Weight	26.0	881.55 g/m ²
Finished Pile Thickness	0.100	2.54 mm
Product Size	24" x 24"	60.96 cm x 60.96 cm
Density	9360	17.43 kilotex
Protective Treatments	SSP® Shaw Soil Protection	
Primary Backing	Non-Woven Synthetic	
Secondary Backing	EcoWorx® Tile	
GSA Approved Product	Yes	

Performance Specifications

Traffic Class	Severe (TARR)
Antimicrobial Assessment	Passes (AATCC-174) (When installed using Shaw 5036 adhesive)
Methanamine Pill Test	Passes (DOCF-1-70)
Radiant Panel	Class I (ASTM E-648)
NBS Smoke	Less than 450 (ASTM-E-662)
Electrostatic Propensity	Less than 3.5 kV (AATCC-134)
CRI Green Label Plus	GLP9968
ADA Compliance	This product meets the guidelines as set forth in the Americans with Disabilities Act for minimum static coefficient of friction of 0.6 for accessible routes.

Warranty Information

Lifetime Commercial Limited

Installation Methods

Monolithic



transforming performance.



Environmental Specifications

Recyclability	100% recyclable
---------------	-----------------

Materials

Ingredients

Surface Treatments	non c8 fluorocarbon chemistry
does not contain PVC, phthalates, or PBD/PBDE	

Recycled Content

Total Recycled Content (by weight)	41.4 %
Pre-Consumer	41.4 %
Post-Consumer	0.0 %
Bio-Based/Rapidly Renewable Content (By Weight)	0.0 %
Packaging	100% Recyclable
Country of Origin (manufacturer)	USA

Meets or exceeds all local and national regulations in country of manufacture.

Manufactured in an ISO9001 & ISO14001 certified facility or equivalent.

Recycled content is calculated using system allocation, mass balance, and direct insertion.

The actual recycled content in this product will likely vary. For more information email info@shawgreenedge.com.

Third Party Certifications

MBDC Cradle to Cradle	Silver Certified
NSF 140	gold certified
CRI Green Label Plus	GLP9968
USGBC LEED	contributes
Building Research Establishment	certified
Good Environmental Choice Australia	certified
Singapore Green Label	Certified 039-003

transforming performance.

On The Right Foot Modular

Product Specifications

Collection Name	Foot in the Door II	
Style Number	I0305	
Product Type	Modular	
Construction	Needlebond Ribbed	
Fiber Type	Polyester	
Dye Method	100% Solution Dyed	
	English	Metric
Gauge	1/12	47.24 per 10 cm
Stitches Per Inch	11	43.31 per 10 cm
Tufted Pile Height	6/32"	4.76mm
Tufted Yarn Weight	50.5	1,712.24 g/m ²
Finished Pile Thickness	.344	8.74 mm
Total Thickness	0.451	11.46 mm
Product Size	24" x 24"	60.96 cm x 60.96 cm
Density	5284	9.84 kilotex
Primary Backing	Woven Synthetic	
Secondary Backing	EcoWorx® Tile	

Performance Specifications

Traffic Class	(TARR)
Antimicrobial Assessment	Passes (AATCC-174) (When installed using Shaw 5036 adhesive)
Methenamine Pill Test	Passes (DOCF-1-70)
Radiant Panel	Class I (ASTM E-648)
NBS Smoke	Less than 450 (ASTM-E-662)
Electrostatic Propensity	Less than 3.5 kV (AATCC-134)
CRI Green Label Plus	certified glp0520
ADA Compliance	This product meets the guidelines as set forth in the Americans with Disabilities Act for minimum static coefficient of friction of 0.6 for accessible routes.

Warranty Information

Lifetime Commercial Limited

Installation Methods

1/4 Turn



transforming performance.



Environmental Specifications

Recyclability	100% recyclable
---------------	-----------------

Materials

Ingredients

does not contain PVC, phthalates, or PBD/PBDE

Recycled Content

Total Recycled Content (by weight)	64 %
Pre-Consumer	39 %
Post-Consumer	25 %
Bio-Based/Rapidly Renewable Content (By Weight)	0 %
Packaging	100% Recyclable
Country of Origin (manufacturer)	USA

Meets or exceeds all local and national regulations in country of manufacture.

Manufactured in an ISO9001 & ISO14001 certified facility or equivalent.

Recycled content is calculated using system allocation, mass balance, and direct insertion.

The actual recycled content in this product will likely vary. For more information email info@shawgreenedge.com.

Third Party Certifications

NSF 140	gold certified
CRI Green Label Plus	certified glp0520
USGBC LEED	contributes

transforming performance.

Lok* Dots™

by Shaw

Shaw Industries, Inc. LokDots™ installation system for carpet tile is a pressure sensitive hot melt adhesive application system for the installation of polyolefin carpet tile. This dry adhesive method allows for ease of installation and installation in high moisture areas. It is designed for polyolefin tiles and should not be used for PVC, felt backed cushion tiles, or tiles that contain plasticizers.

Item	Coverage	Weight
Sleeve (8 rolls) (4 rolls)	250 yds * 125 yds *	3 lb ** 2 lb **
Case (96 rolls)	3,000 yds *	31 lb **
Applicator	NA	2 lb **

* minimum coverage - exception 9 x 36 tiles (8 rolls) 150 yds (4 rolls) 75 yds

** packaged weights

ENVIRONMENTAL

- Certified by Carpet & Rug Institute Green Label Plus GLP 91802
- Silver Certified Cradle to Cradle when used in conjunction with EcoWorx tile products
- Virtually VOC free (<0.1 g/l)

WARRANTY

Life of original installation.

INSTALLATION

For detailed installation instructions, refer to LokDots installation guidelines or call 800.471.7429

Moisture / pH	EcoWorx tile when installed with LokDots does not require Moisture or pH testing.
Approved Subfloors	Concrete, VCT, VAT, Primed Wood, Terrazzo, Raised Access Floors, Cutback, Pressure Sensitive and Multipurpose Adhesive, Advantech

- Assemble required material: LokDots Adhesive Rolls and Handheld Applicator.
- Dry, level and clean floors with no visible moisture.
- Apply dots according to the diagrams featured on the LokDots Installation Guidelines.
- Roll with a 75 lb roller.

For detail on installation, refer to Shaw LokDots Installation Guidelines or www.lokdots.com.

07/2017

transforming performance.

SHAW ADHESIVE 5000
DESCRIPTION: PRESSURE SENSITIVE ADHESIVE

A versatile, water-based, clear acrylic co-polymer adhesive that is solvent free, low odor, contains no hazardous chemicals, and meets the CRI Green Label Plus criteria. Used "Dry" it is a releasable and rebondable adhesive for carpet tiles. #5000 adhesive may be applied to porous or non-porous surfaces and should be allowed to dry completely. Adhesive will be tacky but will not transfer to back of carpet tile. Drying time will vary depending on the temperature, humidity, and porosity of the substrate. This adhesive is not recommended for use over concrete slabs where hydrostatic pressure, excessive moisture or alkali exists. Available in 4-gallon pails.

Application:

Apply adhesive with a 3/8" foam roller for carpet tile installations. Use a 1/16" x 1/16" x 1/16" V notch trowel for 6' wide carpet. **Note:** Do not install carpet into wet adhesive as this will result in a permanent bond and may cause carpet to bubble.

Physical Properties:

V.O.C.: 0 grams per liter (calculated)

Base: Acrylic latex

Color: White

Solids %: 53%

Consistency: Light paste

Open time: Several hours

Coverage: Up to 150-350 sq. ft. per gallon

Shelf Life: Up to one year in unopened container at 70 degrees F

Flammability: Non-flammable, qualified for NFPA Class A and UBC Class 1 fire ratings as determined by the ASTM E84 Tunnel Test

Clean-Up: Use warm, soapy water while wet. When dried, use WFT #9 Adhesive Remover/Stripper.

Other Features: Freeze-thaw stable to 10 degrees F. Low odor.

CAUTION:

Do not take internally. If swallowed, do not induce vomiting. Call a physician immediately.

Warranty:

This adhesive is manufactured according to exacting quality standards and warranted to be free from manufacturing defects. Defective material called to our attention within one year from manufacture will be replaced. No guarantee, expressed or implied is made regarding the performance of this product since the manner and conditions are beyond our control.



MATERIAL SAFETY DATA SHEET

IDENTITY (As shown on label): Shaw 5000 Pressure Sensitive Adhesive

Section I

Prepared by: Todd Bethel

Manufacturer Name: Shaw Industries, Inc.

Address/Phone: P.O. Drawer 2128; Dalton, Ga 30722; (800)441-7429

Emergency Telephone No.: (800)535-5053

Product Class: Synthetic polymer blend

Manufacturer's Code Identification: 5000

Trade Name: Pressure Sensitive Adhesive

Section II

Hazardous Ingredients

None per OSHA Regulation: 29 CFR 1910.1200

SARA Title III Section 313 Chemicals: None

HMIS H=0

F=0

R=0

Section III

Physical Data

Boiling Point: 212°F

LBS/GAL: 8-9

Evaporation Rate: Same as water

Vapor Density: Same as water

Vapor Pressure: Same as water

Percent Volatile by volume: 25% (by weight)

Color: Off White

Odor: Acrylic

Grams V.O.C. per liter of material: 0 (calculated)

Grams V.O.C. per liter of coating: 0 (calculated)

Section IV

Fire & Explosion Hazard Data

Dot Category: Not regulated

Flash Point: None

LEL: N/A

Extinguishing Media: Non-flammable

Unusual Fire & Explosion Hazards: None known

Special Fire Fighting Procedures: None known



Section V

Health Hazard Data Symptoms of Over Exposure

Inhalation: None known

Ingestion: None known

Skin: None known

Eyes: May cause mild irritation

FIRST AID PROCEDURES

Eyes: Flush with water

Skin: Wash with soap and water

Inhalation: Remove to fresh air if needed

Section VI

Reactivity Data

Stability: Stable

Conditions to avoid: None known

Incompatibility-Materials to Avoid: None known

Hazardous decomposition products: None known

Hazardous polymerization: Will not occur

Section VII

Spill or Leak Procedures

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED.

Use absorbent material to collect and contain for salvage or disposal.

Waste Disposal: Abide by all state, federal, and local regulations.

Section VIII

Special Protection Information

Respiratory Protection: None should be needed

Eyes: Goggles

Ventilation: Local exhaust

Protective Gloves: None required

Other Protective Equipment: None

Section IX

Special Precautions

Precaution for handling and storing: Do not puncture

KEEP OUT OF THE REACH OF CHILDREN.